

## TECHNICAL SPECIFICATION SHEET

**Product Designation:**

BRIGHT SILVER 6/25GSM

**Product Code:**

BS6/25

**Manufacturer:**

BRIGHT PACKAGING INDUSTRY BERHAD

**Country of Origin:**

MALAYSIA

**CHARACTERISTIC**

Colour Coating	:	Plain Silver
Description	:	Plain silver Non-Alcohol
Coating Type	:	N.A
Paper Side Laminated	:	Felt side
Foil Side Out	:	Bright Side

**LAMINATED PROPERTY**

Web Weight	Unit	Minimum	Target	Maximum
Paper Weight	gm/m <sup>2</sup>	22.50	25.00	27.50
Adhesive Weight	gm/m <sup>2</sup>	0.80	1.15	1.50
Aluminium Weight	gm/m <sup>2</sup>	14.60	16.20	17.80
Coating Weight	gm/m <sup>2</sup>	0.80	1.10	1.40
<b>Total Weight</b>	<b>gm/m<sup>2</sup></b>	<b>38.70</b>	<b>43.45</b>	<b>48.20</b>
Yield	m <sup>2</sup> /kg	25.84	23.01	20.75

Others	Unit	Value
Tensile Strength (MD)	kN/m	0.98
Tensile Strength (CD)	kN/m	0.65
Moisture	%	5.00
Thickness	µm	0.047
Core ID	mm	58 or 77
Maximum Roll OD	mm	400

**ALUMINIUM / METALIZED PROPERTY**

	Unit	Value
Material	type	Aluminium
Thickness	µm	6
Pinhole	holes/m <sup>2</sup>	Max. 600
Elongation	%	Min. 1
Temper	type	'O' Soft Temper
Alloy	code	A1235

**Chemical Composition**      Wt%

Si	Fe	Cu	Mn	Mg	Zn	Ti	Others	AL
Max. 0.65	Max. 0.65	Max. 0.05	Max. 0.05	Max. 0.05	Max. 0.10	Max. 0.06	Max. 0.03	Min. 99.35

*\*According to aluminium association standard*

PREPARED BY: QUALITY ASSURANCE DEPARTMENT

\*All testing based on industry standard.